



Accessories

Short-stroke pushbuttons KT4F	Z1
Short-stroke pushbuttons KT55	Z2
Short-stroke pushbuttons KT4	Z3
Surface cap K81 and K9 , spacer DS12 , plastic mounting bracket KM1 and socket outlet ST12-16A	Z4
Sealing caps PK18 and PK36 , triple RC module RC12-230V and housing for operating instructions GBA12	Z5

Short-stroke Pushbuttons KT4F

KT4F



Flat short-stroke pushbutton 4 NO contacts 8 A/250 V AC, contact gap 0.5 mm, 80x80 mm external dimensions, internal frame dimensions 63x63 mm, 15 mm high.

The scope of supply comprises the frame R1F, a flat rocker WF, a flat double rocker DWF (all same colour), an attachment frame BRF, the mounting base HP and the pushbutton module.

Fitted using a 55 mm switch box.

We recommend sheet metal countersink screws 2.9x25 mm, DIN 7982 C, for screw connections on 55 mm switch boxes.

The unprinted double rocker is snapped onto the pushbutton module at the factory. If the double rocker is replaced by the large unprinted rocker, remove the rocker halves by pulling off to the front. Do not bend towards the middle. Then snap the large rocker so that the markings 0 and I on the back line up with the same markings on the pushbutton module.

The Eltako frame can be replaced on installation at any time by a design frame with internal dimensions 63x63 mm from other manufacturers.

KT4F-ws	flat short-stroke pushbutton white	EAN 4010312303108	25,10 €/pc.
KT4F-rw	flat short-stroke pushbutton pure white	EAN 4010312303122	25,10 €/pc.
KT4F-sz	flat short-stroke pushbutton black	EAN 4010312303146	25,10 €/pc.
KT4F-an	flat short-stroke pushbutton anthracite	EAN 4010312303177	25,10 €/pc.
KT4F-wg	flat short-stroke pushbutton pure white glossy	EAN 4010312303153	25,10 €/pc.
KT4F-cg	flat short-stroke pushbutton creme white glossy	EAN 4010312311509	25,10 €/pc.
KT4F-si	flat short-stroke pushbutton silvergray glossy	EAN 4010312303351	25,10 €/pc.
KT4F-al	flat short-stroke pushbutton coated/aluminium paint	EAN 4010312311516	32,30 €/pc.
KT4F-sg	flat short-stroke pushbutton black glossy	EAN 4010312311523	32,30 €/pc.

Currently supplied colours of the short-stroke pushbuttons KT4F and their order abbreviations:



ws

rw

sz

an

wg

cg

si

al

sg

Recommended retail prices excluding VAT.

KT55



Short-stroke pushbutton 4 NO contacts 8 A/250 V AC, contact gap 0.5 mm, 80x80 mm external dimensions, internal frame dimensions 55x55 mm, 15 mm high.

The scope of supply comprises the frame R, one large rocker W55, one double rocker DW55 (all same colour), the mounting base HP and the pushbutton module.

Fitted using a 55 mm switch box.

We recommend sheet metal countersink screws 2.9x25 mm, DIN 7982 C, for screw connections on 55 mm switch boxes. See Accessories on page Z-4.

The unprinted double rocker is snapped onto the pushbutton module at the factory. If the double rocker is replaced by the large unprinted rocker, remove the rocker halves by pulling off to the front. Do not bend towards the middle. Then snap the large rocker so that the markings 0 and I on the back line up with the same markings on the pushbutton module.

The Eltako frame can be replaced on installation at any time by a design frame with internal dimensions 55x55 mm from other manufacturers.

KT55-ws	short-stroke pushbutton 55x55 mm, white	EAN 4010312311554	25,10 €/pc.
KT55-rw	short-stroke pushbutton 55x55 mm, pure white	EAN 4010312311592	25,10 €/pc.
KT55-sz	short-stroke pushbutton 55x55 mm, black	EAN 4010312311578	25,10 €/pc.
KT55-an	short-stroke pushbutton 55x55 mm, anthracite	EAN 4010312311585	25,10 €/pc.
KT55-wg	short-stroke pushbutton 55x55 mm, pure white glossy	EAN 4010312311608	25,10 €/pc.
KT55-cg	short-stroke pushbutton 55x55 mm, creme white glossy	EAN 4010312311561	25,10 €/pc.
KT55-si	short-stroke pushbutton 55x55 mm, silvergrey glossy	EAN 4010312311615	25,10 €/pc.
KT55-al	short-stroke pushbutton 55x55 mm, coated/aluminium paint	EAN 4010312311530	32,30 €/pc.
KT55-sg	short-stroke pushbutton 55x55 mm, black glossy	EAN 4010312311547	32,30 €/pc.

Currently supplied colours of the short-stroke pushbuttons KT55 and their order abbreviations:



Short-stroke Pushbuttons KT4

KT4



Short-stroke pushbutton 4 NO contacts 8 A/250 V AC, contact gap 0.5 mm, 80x80 mm external dimensions, internal frame dimensions 55x55 mm, 15 mm high.

The scope of supply comprises the frame R, one large rocker W, one double rocker DW, one intermediate frame ZR (all same colour), the mounting base HP and the pushbutton module.

Fitted using a 55 mm switch box.

We recommend sheet metal countersink screws 2.9x25 mm, DIN 7982 C, for screw connections on 55 mm switch boxes. See Accessories on page Z-4.


The unprinted double rocker is snapped onto the pushbutton module at the factory.

If the double rocker is replaced by the large unprinted rocker, remove the rocker halves by pulling off to the front. Do not bend towards the middle. Then snap the large rocker so that the markings 0 and I on the back line up with the same markings on the pushbutton module.

The Eltako frame can be replaced on installation at any time by a design frame with internal dimensions 55x55 mm from other manufacturers.

KT4-ws	short-stroke pushbutton white	EAN 4010312302910	25,10 €/pc.
KT4-rw	short-stroke pushbutton pure white	EAN 4010312303047	25,10 €/pc.
KT4-sz	short-stroke pushbutton black	EAN 4010312303061	25,10 €/pc.
KT4-an	short-stroke pushbutton anthracite	EAN 4010312303092	25,10 €/pc.
KT4-wg	short-stroke pushbutton pure white glossy	EAN 4010312303078	25,10 €/pc.
KT4-cg	short-stroke pushbutton creme white glossy	EAN 4010312311479	25,10 €/pc.
KT4-si	short-stroke pushbutton silvergrey glossy	EAN 4010312303501	25,10 €/pc.
KT4-al	short-stroke pushbutton coated/aluminium paint	EAN 4010312311486	32,30 €/pc.
KT4-sg	short-stroke pushbutton black glossy	EAN 4010312311493	32,30 €/pc.

Currently supplied colours of the short-stroke pushbuttons KT4 and their order abbreviations:




ws



rw




sz




an




wg




cg



si



al



sg

Recommended retail prices excluding VAT.

Surface cap K81



For series 81,
l x w x h = 60 x 60 x 37 mm.

Surface cap K81

EAN 4010312901236

4,70 €/pc.

Surface cap K9



For series 91,
l x w x h = 60 x 60 x 35 mm.

Surface cap K9

EAN 4010312900734

2,10 €/pc.

Spacer DS12



1/2 module wide = 9 mm, to produce and maintain a ventilation clearance for modular devices dissipating much heat, e.g. dimmers from 300W/400W and continuously rated electromechanical impulse switches.

Spacer DS12

EAN 4010312900987

1,00 €/pc.

Plastic mounting bracket KM1



The KM1 plastic mounting bracket that comes with the device is also available as an individual (accessory) item, e.g. for mounting the light sensor LS.

Plastic mounting bracket KM1

EAN 4010312901311

4,70 €/pc.

Socket outlet ST12-16A



Socket outlet 16A as modular device for mounting on DIN-EN 60715 TH35 rail or as built-in device.
2,5 modules = 45 mm wide, 55 mm deep.

ST12-16A

EAN 4010312700358

18,10 €/pc.

Sealing cap PK18



For all sealable modular devices of series 12 with one module. Covers the back terminals as well as the latched sliding switch and can be sealed. If necessary two sealing caps can be used, one above and one below.

Sealing cap PK18

EAN 4010312901403

1,00 €/pc.

Sealing cap PK36



For single-phase energy meters WSZ12B with 2 modules = 35mm wide and three-phase energy meters without terminal cover clap DSZ12B with 4 modules = 70mm wide. Covers the terminals and can be sealed.

If necessary 1 or 2 sealing caps can be used, one above and one below.

Sealing cap PK36

EAN 4010312901670

1,00 €/pc.

Triple RC module RC12-230V



Modular device for DIN-EN 60715 TH35 rail mounting.
1 module = 18mm wide, 55mm deep.

Used to compensate for inductive interference voltages on control leads. Up to three switchgear devices can be interference-suppressed by connection in parallel with the 230V control inputs.

RC12-230V

EAN 4010312201596

31,70 €/pc.

Housing for operating instructions GBA12



Modular device for DIN-EN 60715 TH35 rail mounting.
1 module = 18mm wide, 55mm deep.

Housing without front panel to insert operating instructions.

GBA12, Housing for operating BA

EAN 4010312901779

1,50 €/pc.