


**S12-400-/310-/220-**



S12-220-230V



### 4-pole 16A/250V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator, for impulse control.  
2 modules = 36 mm wide, 55 mm deep.

Time on: **impulse control only**. Control power demand 12-15 W.

Contacts: 4 NO, 3 NO + 1 NC, 2 NO + 2 NC. Contact gap 3 mm.

**Devices for 25A XS12, page J5.**

**Retrofittable auxiliary contact KM12.**

\* **Non-standard control voltages:** 8, 12, 24, 42, 48, 60, 110V/50Hz or 110, 115, 127 and 220V/60Hz as well as 6, 8, 12, 24, 42, 48, 60, 110 and 220V DC.

Technical data page J7.

<b>S12-400-230V</b> S12-400-*	4 NO 16A 4 NO 16A	EAN 4010312104484	<b>40,70 €/pc.</b> 46,80 €/pc.
<b>S12-310-230V</b> S12-310-*	3 NO + 1 NC 16A 3 NO + 1 NC 16A	EAN 4010312100639	<b>40,70 €/pc.</b> 46,80 €/pc.
<b>S12-220-230V</b> S12-220-*	2 NO + 2 NC 16A 2 NO + 2 NC 16A	EAN 4010312100592	<b>40,70 €/pc.</b> 46,80 €/pc.

Recommended retail prices excluding VAT.