

**R12-100-/200-/110-/020-**



R12-110-230V



## 1- and 2-pole, 16A/250 V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.

1 module = 18 mm wide, 55 mm deep.

100% time on. Control power demand 1.9 W.

Contacts: 1 NO, 2 NO, 1 NO + 1 NC, 2 NC (closed-circuit current relay, 230V only).

Contact gap 3 mm.

Contact/contact test voltage 2000V and control connections/contact test voltage 4000V.

**25A devices XR12, page K4. Retrofittable auxiliary contact KM12, page J3.**

\* **Non-standard control voltages:** 42, 48, 60, 110V/50Hz or 110, 115, 127 and 220V/60Hz as well as 6, 8, 42, 48, 60, 110 and 220V DC.

Technical data page K5.

<b>R12-100-12V</b>	1 NO 16A	EAN 4010312200421	<b>21,30 €/pc.</b>
<b>R12-100-230V</b>	1 NO 16A	EAN 4010312200445	<b>21,30 €/pc.</b>
<b>R12-100-8V, 24V, 12V DC, 24V DC</b>	1 NO 16A		<b>23,00 €/pc.</b>
R12-100-*	1 NO 16A		24,70 €/pc.
<b>R12-200-12V</b>	2 NO 16A	EAN 4010312200506	<b>26,70 €/pc.</b>
<b>R12-200-230V</b>	2 NO 16A	EAN 4010312200520	<b>26,70 €/pc.</b>
<b>R12-200-8V, 24V, 12V DC, 24V DC</b>	2 NO 16A		<b>28,50 €/pc.</b>
R12-200-*	2 NO 16A		30,60 €/pc.
<b>R12-110-12V</b>	1 NO + 1 NC 16A	EAN 4010312200469	<b>26,70 €/pc.</b>
<b>R12-110-230V</b>	1 NO + 1 NC 16A	EAN 4010312200483	<b>26,70 €/pc.</b>
<b>R12-110-8V, 24V, 12V DC, 24V DC</b>	1 NO + 1 NC 16A		<b>28,50 €/pc.</b>
R12-110-*	1 NO + 1 NC 16A		30,60 €/pc.
<b>R12-020-230V</b>	2 NC 16A	EAN 4010312201572	<b>26,70 €/pc.</b>

Recommended retail prices excluding VAT.