


**R12-400-/310-/220-**



R12-400-230V



## 4-pole, 16 A/250 V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.

2 modules = 36 mm wide, 55 mm deep.

100 % time on. Control power demand 4 W.

Contacts: 4 NO, 3 NO + 1 NC, 2 NO + 2 NC.

Contact gap 3 mm.

Contact/contact test voltage 2000V and control connections/contact test voltage 4000V.

**25A devices XR12, page K4. Retrofittable auxiliary contact KM12, page J3.**

**\* Non-standard control voltages:** 8, 12, 24, 42, 48, 60 and 110V/50Hz or 110, 115, 127 and 220V/60Hz as well as 6, 8, 12, 24, 42, 48, 60, 110 and 220V DC.

Technical data page K5.

<b>R12-400-230V</b> R12-400-*	4 NO 16A 4 NO 16A	EAN 4010312200643	<b>40,70 €/pc.</b> 46,80 €/pc.
<b>R12-310-230V</b> R12-310-*	3 NO + 1 NC 16A 3 NO + 1 NC 16A	EAN 4010312200605	<b>40,70 €/pc.</b> 46,80 €/pc.
<b>R12-220-230V</b> R12-220-*	2 NO + 2 NC 16A 2 NO + 2 NC 16A	EAN 4010312200568	<b>40,70 €/pc.</b> 46,80 €/pc.