


**R81-001-/002-**



R81-002-230V



### 1 or 2 CO contacts 10A/250V AC

Built-in devices for installation and surface mounting.

50 mm long, 42 mm wide, 32 mm deep.

Time on 100%. Control power demand 5-5.5 W.

Contact gap 2 mm.

Contact/contact test voltage 2000V and control connection/contact test voltage 4000V.

\* **Non-standard control voltages:** 8, 24, 42, 48, 60 and 110V/50Hz or 110, 115, 127 and 220V/60Hz as well as 6, 8, 12, 24, 42, 48, 60, 110 and 220V DC.

Technical data page K5.

|                     |          |                   |                    |
|---------------------|----------|-------------------|--------------------|
| <b>R81-001-12V</b>  | 1 CO 10A | EAN 4010312203064 | <b>21,90 €/pc.</b> |
| <b>R81-001-230V</b> | 1 CO 10A | EAN 4010312203088 | <b>21,90 €/pc.</b> |
| R81-001-*           | 1 CO 10A |                   | 25,40 €/pc.        |
| <b>R81-002-12V</b>  | 2 CO 10A | EAN 4010312203026 | <b>26,70 €/pc.</b> |
| <b>R81-002-230V</b> | 2 CO 10A | EAN 4010312203040 | <b>26,70 €/pc.</b> |
| R81-002-*           | 2 CO 10A |                   | 30,60 €/pc.        |