


XR12-400-/310-/220-



4-pole, 25 A/250 V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.

2 modules = 36 mm wide, 55 mm deep.

100% time on. Control power demand 4 W.

Contacts: 4 NO, 3 NO + 1 NC, 2 NO + 2 NC.

Contact gap 3 mm.

Contact/contact test voltage 2000V and control connection/contact test voltage 4000V.

Retrofittable auxiliary contact KM12, page J3.

XR12-400-230V

Technical data page K5.

| | | | |
|------------------------|-----------------|-------------------|--------------------|
| XR12-400-12V | 4 NO 25A | EAN 4010312201350 | 46,30 €/pc. |
| XR12-400-24V | 4 NO 25A | EAN 4010312201367 | 46,30 €/pc. |
| XR12-400-230V | 4 NO 25A | EAN 4010312201374 | 40,70 €/pc. |
| XR12-400-12V DC | 4 NO 25A | EAN 4010312202913 | 46,30 €/pc. |
| XR12-400-24V DC | 4 NO 25A | EAN 4010312201381 | 46,30 €/pc. |
| XR12-310-12V | 3 NO + 1 NC 25A | EAN 4010312201404 | 46,30 €/pc. |
| XR12-310-24V | 3 NO + 1 NC 25A | EAN 4010312201411 | 46,30 €/pc. |
| XR12-310-230V | 3 NO + 1 NC 25A | EAN 4010312201428 | 40,70 €/pc. |
| XR12-310-12V DC | 3 NO + 1 NC 25A | EAN 4010312203217 | 46,30 €/pc. |
| XR12-310-24V DC | 3 NO + 1 NC 25A | EAN 4010312201435 | 46,30 €/pc. |
| XR12-220-12V | 2 NO + 2 NC 25A | EAN 4010312201459 | 46,30 €/pc. |
| XR12-220-24V | 2 NO + 2 NC 25A | EAN 4010312201466 | 46,30 €/pc. |
| XR12-220-230V | 2 NO + 2 NC 25A | EAN 4010312201473 | 40,70 €/pc. |
| XR12-220-12V DC | 2 NO + 2 NC 25A | EAN 4010312202906 | 46,30 €/pc. |
| XR12-220-24V DC | 2 NO + 2 NC 25A | EAN 4010312201480 | 46,30 €/pc. |

Recommended retail prices excluding VAT.