



30 000 970 - 3

IR scanner for energy meter data gateway FSDG14

AIR

Temperature at mounting location:
0°C up to +50°C.
Storage temperature: -25°C up to +70°C.
Relative humidity:
annual average value <75%.

valid for devices from production week 31/20 (see bottom side of housing)

Magnetic infrared opto head for reading out electronic energy meters with IEC 62056-21 IR interface.

The scope of supply comprises the infrared opto head with cables for connection to the terminals of the data gateway FSDG14.

The AIR data interface is an infrared RS232 interface acc. to IEC 1107 or EN61107 specification with a magnetic head. The interface serves as a data-side connecting unit between the infrared port of the energy meter and the serial input of the FSDG14 data gateway. Open, tinned cable ends for connection to the terminals of the data gateway FSDG14. Cable length 0.75 m.

Technical data

Supply voltage	+12 V DC (±10%)
Supply by FSDG14	
Current consumption	10 mA
Function indicator	green LED
Data transmission	yellow LED
Cable colours	+12 V = brown/white, GND = white/white, Rx = green/white
Rate of transmission	9600 Baud
Wave length	940 nm
Dimensions	Ø 32 mm Height 29 mm Length without cable 34 mm
Protection class	IP50

Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

Technical Support English:

+49 711 94350025

technical-support@eltako.de

eltako.com

31/2020 Subject to change without notice.