


Wireless sensor without battery
or wire 

Wireless flat pushbutton in E-design
FIFT65

Temperature at mounting location:
-20°C up to +50°C.
Storage temperature: -25°C up to +70°C.
Relative humidity:
annual average value <75%.

Wireless flat pushbutton for single
mounting 84x84x11 mm or mounting
into the E-design switching system.
Generates the power for wireless tele-
grams itself when the button is pressed,
therefore there is no connecting wire
and no standby loss.

The scope of supply comprises the flat
frame RFIE, a rocker, a mounting base,
the wireless module and one adhesive foil.


Wireless flat pushbuttons with one rocker
can send an analysable signal. Press
the bottom of the rocker near the mark.

The mounting base can be screwed onto
a flat surface or glued to the wall, on
glass or on furniture using the enclosed
adhesive foil. Use the sleeves in the
55 mm socket box for screw mounting.

Before screwing on the device, remove
the rocker and remove the frame from the
mounting plate. Then screw on the
mounting base - with the 'top' marking
pointing upwards. Snap the frame and
rocker back in.

We recommend stainless-steel counter-
sunk screws 2.9x25 mm, DIN 7982 C,
for screw connections. Both with rawl
plugs 5x25 mm and with 55 mm switch
boxes.

**The wireless module integrated in the
wireless flat pushbutton can be taught-in
encrypted as described in the operating
instructions in all encryptable actuators
of the Series 61 and Series 71 as well
as the FAM14. This requires the wireless
encryption plug FVST.**



Encryptable actuators bear the pictogram


Teaching-in wireless sensors in wireless actuators

**All sensors must be taught-in in the
actuators so that they can detect and
execute commands.**



The teach-in process is described in the
operation manual of the actuators.

Activate encryption:



*Insert the encryption plug and operate
the rocker.*

Deactivate encryption:



*Insert the encryption plug and operate
the rocker.*

EnOcean wireless

Frequency	868.3 MHz
Transmit power	max. 10 mW

**Hereby, Eltako GmbH declares that the
radio equipment type FIFT65 is in compliance
with Directive 2014/53/EU.**


**The full text of the EU declaration of
conformity is available at the following
internet address: eltako.com**

Must be kept for later use!


Eltako GmbH


D-70736 Fellbach

Technical Support English:

 Michael Thünte +49 176 13582514

 thuente@eltako.de

 Marc Peter +49 173 3180368

 marc.peter@eltako.de

eltako.com