




30 000 451 - 1



Wireless 1-way pushbutton without battery and wire FIT80-



Temperature at mounting location:
-20°C up to +50°C.
Storage temperature: -25°C up to +70°C.
Relative humidity:
annual average value <75%.

**Wireless 1-way pushbutton 80x40x15 mm,
with energy generator. Generates the energy
for radio telegrams by pushing the button,
therefore without connecting cable and no
stand-by loss.**

The wireless 1-way pushbutton transmits
1 signal that can be evaluated.

It can be screwed onto a flat surface or glued
to the wall using the enclosed adhesive foil.

Before screwing on, the housing must be
opened and the prepared holes in the holding
plate must be pierced with a pointed object.

Set of 2 stainless-steel counter-sunk screws
2,9x25 mm and plugs 5x25 mm are enclosed.

Technical data

Protection degree IP54 (Dust and
splash water protection)

Wireless telegrams according to EEP F6-01-01
ORG = 0x05

Data_byte3 = push = 0x10
release = 0x00



enocean®

THE UNIQUE WIRELESS PROFESSIONAL
SMART HOME STANDARD

Frequency 868.3 MHz

Transmit power max. 10 mW

**Hereby, Eltako GmbH declares that the radio
equipment type FIT80- is in compliance
with Directive 2014/53/EU.**

**The full text of the EU declaration of
conformity is available at the following
internet address: eltako.com**

Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

Technical Support English:

+49 711 943 500 25

technical-support@eltako.de

eltako.com

10/2022 Subject to change without notice.