

Wireless 2-way central control flat pushbutton with battery



F2FZT65B-wg

Temperature at mounting location:
-20°C up to +50°C.
Storage temperature: -25°C up to +70°C.
Relative humidity:
annual average value <75%.

Wireless 2-way flat pushbutton for single mounting 84x84x11mm or mounting into the E-design switching system. Silent and with battery (lifetime 5-8 years). With rocker laser engraved. Smart Home sensor.

The scope of supply comprises a mounting base with snapped-on electronics, a frame RFIE and a rocker.


Wireless pushbuttons with one rocker can transmit two evaluable signals: press rocker up and press rocker down. The mounting base can be screwed onto a flat surface or glued to the wall, on glass or on furniture using the enclosed adhesive foil. Use the sleeves in the 55mm socket box for screw mounting. Snap the large rocker so that the markings 0 and I on the back line up with the same markings on the wireless module.

Installation only on a level surface:

Screw on or glue mounting plate. First snap on the electronics, then the frame and remove the battery insulator. When you fit the rocker, the 0 mark on the rear must always be on top sein.

We recommend stainless-steel counter-sunk screws 2.9x25mm, DIN 7982 C, for screw connections. Both with rawl plugs 5x25mm and with 55mm switch boxes.

All you need to do to change the CR2032 button cell is remove the rocker.

The electronics integrated in the wireless pushbutton can be taught-in encrypted as described in the operating instructions in all encryptable actuators of the Series 61 and Series 71 as well as the FAM14. Encryptable actuators bear the pictogram .

Activate encryption:

Activate encryption: Insert the supplied encryption plug between the left pad V and the middle pad (V 0-0 0) into the circuit board and press a rocker.

Deactivate encryption:

Insert the supplied encryption plug between the right pad N and the middle pad (0 0-0 N) into the circuit board and press a rocker.

Teaching-in wireless sensors in wireless actuators

All sensors must be taught-in in the actuators so that they can detect and execute commands.

The teach-in process is described in the operation manual of the actuators.

The crossed-out waste container indicates that batteries may not be disposed with other household or commercial waste.

Batteries can be returned free of charge to the retail outlet after use.



Attention: Danger of explosion if battery is replaced improperly. Only replace it by an equivalent type!

EnOcean wireless

Frequency	868.3 MHz
Transmit power	max. 10mW

Hereby, Eltako GmbH declares that the radio equipment type F2FZT65B is in compliance with Directive 2014/53/EU.


The full text of the EU declaration of conformity is available at the following internet address: eltako.com

Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

Technical Support English:

 Michael Thünte +49 176 13582514

 thuente@eltako.de

 Marc Peter +49 173 3180368

 marc.peter@eltako.de

eltako.com