




30 055 432 - 1



## Wireless 4-way profile pushbutton

F4PT55E-@



Temperature at mounting location:  
-20°C up to +50°C.

Storage temperature: -25°C up to +70°C.

Relative humidity:  
annual average value <75%.

**Wireless 4-way profile pushbutton for single mounting 80x80x15 mm or mounting in the E-Design55 switching system.**

**Generates the power for wireless telegrams itself when the button is pressed, therefore there is no connecting wire and no standby loss. Smart Home Sensor.**

**With double rocker laser engraved with 'Home Day/ Night', 'Away' and 'Holiday' each in the selected language and colour.**

Wireless pushbuttons with double rocker can transmit four evaluable signals: press two rockers up or down.

The mounting base can be screwed onto a flat surface or glued to the wall, on glass or on furniture using the enclosed adhesive foil. Use the sleeves in the 55 mm socket box for screw mounting.

**Adhesion:** First adhere the set *comprising the mounting base, frame and attachment frame* - with the latches pointing at the top and bottom. Then snap on the set *comprising the wireless module and rocker* - with the marking 0 on the back always pointing up.

**Before screwing,** remove the mounting base from the frame and the attachment frame. To do this, press the latches on the mounting base outwards. Then screw the mounting base - with the latches at top and bottom -, snap on the frame with the attachment frame and snap on the set *comprising the wireless module and rocker* - with the marking 0 on the back always pointing to the top.

We recommend stainless-steel counter-sunk screws 2.9x25 mm, DIN 7982 C, for screw connections. Both with rawl plugs

5x25 mm and with 55 mm switch boxes.

The electronics integrated in the wireless pushbutton can be taught-in encrypted as described in the operating instructions in all encryptable actuators of the Series 61, 62 and Series 71 as well as the FAM14. This requires the FTWV wireless pushbutton encryption rocker. Encryptable actuators bear the pictogram

### Teaching-in wireless sensors in wireless actuators

**All sensors must be taught-in in the actuators so that they can detect and execute commands.**

The teach-in process is described in the operation manual of the actuators.



**enocean®**

THE UNIQUE WIRELESS PROFESSIONAL  
SMART HOME STANDARD

Frequency	868.3 MHz
Transmit power	max. 10 mW

**Hereby, Eltako GmbH declares that the radio equipment type F4PT55E-@ is in compliance with Directive 2014/53/EU.**

**The full text of the EU declaration of conformity is available at the following internet address: [eltako.com](http://eltako.com)**

**Must be kept for later use!**

### **Eltako GmbH**

D-70736 Fellbach

**Technical Support English:**

+49 711 943 500 25

[technical-support@eltako.de](mailto:technical-support@eltako.de)

[eltako.com](http://eltako.com)

07/2022 Subject to change without notice.