

Wireless handheld transmitter
without battery or wire with
double rocker



FHS4-al/anso

Temperature at mounting location:

-20°C up to +50°C.

Storage temperature: -25°C up to +70°C.

Relative humidity:

annual average value <75%.

Wireless 4-way hand-held transmitter with double rocker aluminium/anthracite-soft, 49x47 mm, 16mm high. Weighs only 37 grams. Generates the power for wireless telegrams itself when the button is pressed, therefore there is no battery. Smart Home sensor.

The batteryless hand-held transmitter FHS4 contains one wireless module with a laser engraved double rocker.

Therefore it can transmit 4 evaluable wireless telegrams.

The bottom is painted in aluminum and the rockers have an anthracite soft paint.

The wireless module integrated in the hand-held wireless transmitter can be taught-in encrypted in all encryptable actuators of the Series 61 and Series 71 as well as the FAM14. This requires the FTVW wireless pushbutton encryption rocker.

Then lock again the radio module marked 0 at the top.

After that, clip the rockers marked 1 & 3 left and 2 & 4 right on the radio module.

Encryptable actuators bear the pictogram .



EnOcean wireless

Frequency	868.3 MHz
Transmit power	max. 10 mW


Hereby, Eltako GmbH declares that the radio equipment type FHS2-al/anso is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following internet address: eltako.com


Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

Technical Support English:

 +49 711 94350025

 technical-support@eltako.de

eltako.com