



30 000 420 - 1

Wireless and batteryless
bell pushbutton

FKD-



Temperature at mounting location:
-20°C up to +50°C.
Storage temperature: -25°C up to +70°C.
Relative humidity:
annual average value <75%.

**Wireless bell pushbutton 80x40x15 mm,
with energy generator. Generates the energy
for radio telegrams by pushing the button,
therefore without connecting cable and no
stand-by loss.**

Labeling field 43x12 mm. For example for
Dymo label tape 9 mm and 12 mm.

The radio bell pushbutton transmits 1 signal
that can be evaluated like a 1-way wireless
pushbutton.

The FKD can be screwed onto a flat surface or
glued to the wall using the enclosed adhesive
foil.

Before screwing on, the housing must be
opened and the prepared holes in the holding
plate must be pierced with a pointed object.
Set of 2 stainless-steel counter-sunk screws
2,9x25 mm and plugs 5x25 mm are enclosed.

Technical data

Protection degree	IP54 (Dust and splash water protection)
-------------------	---

Wireless telegrams according to EEP F6-01-01

ORG = 0x05

Data_byte3 = push = 0x10

release = 0x00



enocean®

THE UNIQUE WIRELESS **PROFESSIONAL
SMART HOME** STANDARD

Frequency	868.3 MHz
-----------	-----------

Transmit power	max. 10 mW
----------------	------------

**Hereby, Eltako GmbH declares that the radio
equipment type FKD- is in compliance with
Directive 2014/53/EU.**

**The full text of the EU declaration of
conformity is available at the following
internet address: eltako.com**

Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

Technical Support English:

+49 711 94350025

technical-support@eltako.de

eltako.com

26/2020 Subject to change without notice.