

Wireless sensor Key card switch FKF65

Eltako



Temperature at mounting location:
-20°C up to +50°C.
Storage temperature: -25°C up to +70°C.
Relative humidity:
annual average value <75%.

Wireless card switch for surface mounting 84x84x29 mm.

When the hotel key card in standard bank card format 86x54 mm is inserted and removed, a wireless telegram is sent over the Eltako wireless network.

The scope of supply contains the completely assembled two-part card guide, an R1E frame, a mounting frame, a mounting plate, a wireless module and two screws with rawl plugs.

Fitting by screwing

First dismantle the fully assembled card switch. To do this, remove the screw, unhook the card guide and remove the intermediate frame together with the transmitter module by loosening the retaining bars at the top and bottom.

Fit the mounting plate by tightening the screws. Engage the frame together with the hook-in cut-outs at the top and the intermediate frame including the transmitter module with the rear ID 0 upwards. Insert the card guide into the top hook-in cut-outs of the frame and screw tight into the retaining plate using the screw at the bottom.

Worn card guides can be easily replaced without changing the transmitter module.

The wireless module integrated in the wireless card switch can be taught-in encrypted as described in the operating instructions in all encryptable actuators of the Series 61, 62 and 71 and FAM14. This requires the FTVW wireless pushbutton encryption rocker. Encryptable actuators bear the pictogram .

Teaching-in wireless sensors in wireless actuators

All sensors must be taught-in in the actuators so that they can detect and execute commands.

The teach-in process is described in the operation manual of the actuators.

The key card switch is taught-in like a pushbutton when a card is inserted.

Wireless telegram according to EEP F6-01-01
ORG = 0x05

Data_byte3 = 0x10 insert card
0x00 remove card

Manuals and documents in further languages



<http://eltako.com/redirect/FKF65-wg>



THE UNIQUE WIRELESS PROFESSIONAL SMART HOME STANDARD

Frequency	868.3 MHz
Transmit power	max. 10 mW

Hereby, Eltako GmbH declares that the radio equipment type FKF65 is in compliance with Directive 2014/53/EU.

The full text of the EU declaration of conformity can be accessed via the QR code or the internet address under 'Documents'.

Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

Technical Support English:

☎ +49 711 943 500 25

✉ technical-support@eltako.de

eltako.com