



30 000 467 - 1

Wireless mini handheld transmitter

FMH1W-anso



Temperature at mounting location:

-20°C up to +50°C.

Storage temperature: -25°C up to +70°C.

Relative humidity:

annual average value <75%.

Wireless mini handheld transmitter waterproof 72 x 30 mm, 15 mm high. Weighs only 34 grams. Generates the power for wireless telegrams itself when the button is pressed, therefore there is no battery. Smart Home sensor.

With anthracite-soft paint.

Suitable as a keychain.

The Wireless mini handheld transmitter transmits 1 signal that can be evaluated like a 1-way wireless pushbutton.

Teaching-in wireless sensors in wireless actuators

All sensors must be taught-in in the actuators so that they can detect and execute commands.

The teach-in process is described in the operation manual of the actuators.

Technical data

Protection degree IP54 (Dust and splash water protection)

Wireless telegrams according to EEP F6-01-01
ORG = 0x05

Data_byte3 = push = 0x10
release = 0x00



enocean®

THE UNIQUE WIRELESS **PROFESSIONAL**
SMART HOME STANDARD

Frequency 868.3 MHz

Transmit power max. 10 mW

Hereby, Eltako GmbH declares that the radio equipment type FMH1W-anso is in compliance with Directive 2014/53/EU.

The full text of the EU declaration of conformity is available at the following internet address: eltako.com

Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

Technical Support English:

+49 711 94350025

technical-support@eltako.de

eltako.com

36/2021 Subject to change without notice.