



30 000 465 - 1



Wireless mini handheld transmitter

FMH1W-wg/rot



Temperature at mounting location:
 -20°C up to +50°C.
 Storage temperature: -25°C up to +70°C.
 Relative humidity:
 annual average value <75%.

Wireless mini handheld transmitter for calling systems 72 x 30 mm, 15 mm high. Weighs only 34 grams. Generates the power for wireless telegrams itself when the button is pressed, therefore there is no battery. Smart Home sensor.

With red button and grey carry strap.

The Wireless mini handheld transmitter transmits 1 signal that can be evaluated like a 1-way wireless pushbutton.

Teaching-in wireless sensors in wireless actuators

All sensors must be taught-in in the actuators so that they can detect and execute commands.

The teach-in process is described in the operation manual of the actuators.

Technical data

Protection degree	IP54 (Dust and splash water protection)
-------------------	---

Wireless telegrams according to EEP F6-01-01
 ORG = 0x05
 Data_byte3 = push = 0x10
 release = 0x00



enocean®

THE UNIQUE WIRELESS **PROFESSIONAL SMART HOME** STANDARD

Frequency	868.3 MHz
Transmit power	max. 10 mW

Hereby, Eltako GmbH declares that the radio equipment type FMH1W-wg/rot is in compliance with Directive 2014/53/EU.

The full text of the EU declaration of conformity is available at the following internet address: eltako.com

Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

Technical Support English:

+49 711 94350025

technical-support@eltako.de

eltako.com

36/2021 Subject to change without notice.