

Wireless socket repeater



FSRP-230V

Only skilled electricians may install this electrical equipment otherwise there is the risk of fire or electric shock!

Temperature at mounting location:

0°C up to +35°C.

Storage temperature: -25°C up to +70°C.

Relative humidity:

annual average value <75%.

1- and 2-level wireless socket repeater.

Only 0.9 watt standby loss.

Adapter for German fused safety socket.

With increased shock protection.

This repeater is only needed if the building conditions do not allow undisturbed reception or the distance between the wireless pushbutton and receiver is too great.

The 1-level mode is activated ex works.

Only the signals are received, tested and retransmitted at full transmit power.

Wireless signals from other repeaters are ignored to reduce the data volume.

To switch to the 2-level mode, the *level 2* button has to be pressed for 3 seconds.

Now the wireless signals of another 1-level repeater are being processed.

Thereby a signal can be received and amplified with a maximum of two times.

To return back to the 1-level mode, the *level 1* button has to be pressed for 3 seconds.

Wireless repeaters need not be taught-in.

They receive and amplify signals from all wireless sensors within their reception area.

The LED indicates received wireless telegrams by briefly flashing during operation.

Technical data

Rated voltage	230V AC/50 Hz
Rated current	16A
Ambient temperature range	0-35°C



May only be used in closed dry rooms.

The socket must be easily accessible.

Don't insert in a row.

ELTAKO GmbH hereby declares that the products that relates to this operating manual, are in compliance with the essential requirements and other relevant provisions of directive 1999/5/EC. A copy of the EU declaration of conformity can be requested at the address below.

WEEE registration number DE 30298319

Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

+49 711 94350000

www.eltako.com