

Wireless pushbuttons Bticino



FT4BI

Temperature at mounting location:

-20°C up to +50°C.

Storage temperature: -25°C up to +70°C.

Relative humidity:

annual average value <75%.

Wireless pushbuttons for internal frame dimensions 43x43 mm, Bticino.

Generates the power for wireless telegrams itself when the button is pressed, therefore there is no connecting wire and no standby loss.

The scope of supply comprises a rocker, a double rocker, the mounting base (all same colour), the wireless module and one adhesive foil.

Wireless pushbuttons with one rocker

can transmit two evaluable signals:

press rocker up and press rocker down.

Wireless pushbuttons with double rocker

can transmit four evaluable signals:

press two rockers up or down.

The mounting base can be screwed onto a flat surface or glued to the wall, on glass or on furniture using the enclosed adhesive foil. Use the sleeves in the 55 mm socket box for screw mounting.

The double rocker is snapped onto the wireless module at the factory. If the double rocker is replaced by the rocker, remove the rocker halves by pulling off to the front. Do not bend towards the middle. Then snap the rocker so that the markings 0 and I on the back line up with the same markings on the wireless module.

Frames

The frame is not included, please order it from Bticino.

Teaching-in wireless sensors in wireless actuators

All sensors must be taught-in in the actuators so that they can detect and execute commands.

The teach-in process is described in the operation manual of the actuators.

Look also the catalogue "Eltako – The System in the Building".

EnOcean wireless

Frequency	868.3 MHz
Transmit power	max. 10 mW

Hereby, Eltako GmbH declares that the radio equipment type FT4BI is in compliance with Directive 2014/53/EU.

The full text of the EU declaration of conformity is available at the following internet address: eltako.com

Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

Technical Support English:

☎ Michael Thünte +49 176 13582514

✉ thuente@eltako.de

☎ Marc Peter +49 173 3180368

✉ marc.peter@eltako.de

eltako.com