

Tap-radio® rocker pushbutton



TF-WTB55

Temperature at mounting location:  
-20°C up to +50°C.  
Storage temperature: -25°C up to +70°C.  
Relative humidity:  
annual average value <75%.

1-way wireless rocker pushbutton pure white glossy for single mounting 84x84x19 mm or mounting into the E-design switching system. With battery (lifetime 5-8 years). Smart Home sensor.

Independent of the respective tilting position an evaluable signal is generated by pressing and the light switches on and off like an conventional switch.

The mounting base can be screwed onto a flat surface or glued to the wall, on glass or on furniture using the enclosed adhesive foil. Use the sleeves in the 55 mm socket box for screw mounting.

**Installation only on a level surface:**

Screw on or glue mounting plate. First snap on the frame and then clip on the attachment frame with the electronics. Insert the enclosed button cell in the battery compartment with the + marking pointing upwards. When you fit the rocker, the 0 mark on the rear must always be on top.

We recommend stainless-steel counter-sunk screws 2,9x25 mm, DIN 7982 C, for screw connections. Both with rawl plugs 5x25 mm and with 55 mm switch boxes.

**To change the button cell CR2032, the rocker has to be removed.**

**Teaching-in wireless sensors in wireless actuators**

**All sensors must be taught-in in the actuators so that they can detect and execute commands.**

The teach-in process is described in the operation manual of the actuators.

**The crossed-out waste container indicates that batteries may not be disposed with other household or commercial waste. Batteries can be returned free of charge to the retail outlet after use.**



**Attention: Danger of explosion if battery is replaced improperly. Only replace it by an equivalent type!**

**EnOcean wireless**

Frequency	868.3 MHz
Transmit power	max. 10 mW

**Hereby, Eltako GmbH declares that the radio equipment type TF-WTB is in compliance with Directive 2014/53/EU.**

**The full text of the EU declaration of conformity is available at the following internet address: [eltako.com](http://eltako.com)**

**Must be kept for later use!**

**Eltako GmbH**

D-70736 Fellbach

**Technical Support English:**

☎ Michael Thünte +49 176 13582514

✉ [thuente@eltako.de](mailto:thuente@eltako.de)

☎ Marc Peter +49 173 3180368

✉ [marc.peter@eltako.de](mailto:marc.peter@eltako.de)

[eltako.com](http://eltako.com)