

Tap-radio® repeater adapter



TF100P-230V

Ambient temperature:

0°C up to +35°C.

Storage temperature: -25°C up to +70°C.

Relative humidity:

annual average value <75%.

Wireless repeater adapter level 1.

100x55x45 mm (measurements without plug), pure white glossy. Standby loss only 0.8 watt.

Adapter for German fused safety sockets.

A repeater is only required if the building structure permits undisturbed reception or the distance between the sensor and actuator is too large. Only telegrams from sensors and actuators are received and sent with full transmit power, but not the telegrams of other repeaters.

Technical data

Rated voltage	230V AC/50Hz
Rated current	16A
Ambient temperature	0°C up to +35°C



May only be used in closed dry rooms.

The socket must be easily accessible.

Don't insert in a row.

EnOcean wireless

Frequency	868,3 MHz
Transmit power	max. 10 mW

Hereby, Eltako GmbH declares that the radio equipment type TF100P-230V is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following internet address: eltako.com


WEEE registration number DE 30298319


Must be kept for later use!


Eltako GmbH

D-70736 Fellbach

Technical Support English:

 Michael Thünte +49 176 13582514

 thuente@eltako.de

 Marc Peter +49 173 3180368

 marc.peter@eltako.de

eltako.com