

Tap-radio® repeater adapter



TF100R-230V

Ambient temperature:

0°C up to +35°C.

Storage temperature: -25°C up to +70°C.

Relative humidity:

annual average value <75%.

Wireless repeater adapter level 1.

100x55x45 mm (measurements without plug), pure white glossy. Standby loss only 0.8 watt.

Adapter for German fused safety sockets.

A repeater is only required if the building structure permits undisturbed reception or the distance between the sensor and actuator is too large. Only telegrams from sensors and actuators are received and sent with full transmit power, but not the telegrams of other repeaters.

Technical data

Rated voltage	230V AC/50Hz
---------------	--------------

Rated current	16A
---------------	-----

Ambient temperature	0°C up to +35°C
---------------------	-----------------

**May only be used in closed dry rooms.****The socket must be easily accessible.****Don't insert in a row.**

ELTAKO GmbH hereby declares that the products that relates to this operating manual, are in compliance with the essential requirements and other relevant provisions of directive 1999/5/EC. A copy of the EU declaration of conformity can be requested at the address below.

WEEE registration number DE 30298319

Must be kept for later use!**Eltako GmbH**

D-70736 Fellbach

Technical Support English:

Michael Thünte +49 176 13582514

thuente@eltako.de

Marc Peter +49 173 3180368

marc.peter@eltako.deeltako.com