



30 055 712 - 1

Eltako

Manuals and documents in further languages



<http://eltako.com/redirect/W2T55E->

Rocker pushbutton W2T55E-

Only skilled electricians may install this electrical equipment otherwise there is the risk of fire or electric shock!

Temperature at mounting location:
-20°C up to +50°C.
Storage temperature: -25°C up to +70°C.
Relative humidity:
annual average value <75%.

**Rocker pushbutton, 2 NO contacts
10 A/250 V AC. Pushbutton for single
mounting, 80 x 80 x 18 mm.**


**The scope of supply comprises the frame
R1UE55, an attachment frame, one double
rocker W2T55E- and the rocker pushbutton
insert.**

The rocker pushbutton with VDE sign has
plug-in terminals.

Alternatively to claw fixing, screw fixing
is also available for 55 mm switch boxes
with stainless steel countersunk screws
2.9 x 25 mm, DIN 7982 C.

Installation: Fit rocker pushbutton, fix
frame using attachment frame and plug on
rocker.

Wiring diagram



1. App 2.  3. **www.**


Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

Technical Support English:

 +49 711 943 500 25

 technical-support@eltako.de

eltako.com

25/2022 Subject to change without notice.