

Rocker switch



WS55

**Only skilled electricians may install this electrical equipment otherwise there is the risk of fire or electric shock!**

Temperature at mounting location:

-20°C up to +50°C.

Storage temperature: -25°C up to +70°C.

Relative humidity:

annual average value <75%.

Rocker switch, 1 CO contact 10A/250V AC.  
Switch for single mounting 80x80mm  
external dimensions, internal frame  
dimensions 55x55 mm, 15 mm high.


The scope of supply comprises the  
frame R, one rocker W55 and the rocker  
switch insert.

The rocker switch with VDE sign has  
plug-in terminals.

Alternatively to claw fixing, screw fixing  
is also available for 55 mm switch  
boxes with stainless steel countersunk  
screws 2.9x25 mm, DIN 7982 C.

**Installation:** Fit rocker pushbutton, fix  
frame using attachment frame and plug  
on rocker.

### Wiring diagram



**Must be kept for later use!**

## Eltako GmbH

D-70736 Fellbach

### Technical Support English:

☎ Michael Thünte +49 176 13582514

✉ [thuente@eltako.de](mailto:thuente@eltako.de)

☎ Marc Peter +49 173 3180368

✉ [marc.peter@eltako.de](mailto:marc.peter@eltako.de)

[eltako.com](http://eltako.com)