

# Rocker pushbutton WT65



**Only skilled electricians may install this electrical equipment otherwise there is the risk of fire or electric shock!**

Temperature at mounting location:

-20°C up to +50°C.

Storage temperature: -25°C up to +70°C.

Relative humidity:

annual average value <75%.

Rocker pushbutton, 1 NO contact  
10A/250V/AC. Pushbutton for individual  
installation 84x84x22 mm or installation  
in the E-Design switch system.


The scope of supply comprises the R1E  
frame, a rocker, an attachment frame  
and the rocker pushbutton.

The rocker pushbutton with VDE sign  
has plug-in terminals.

Alternatively to claw fixing, screw fixing  
is also available for 55 mm switch  
boxes with stainless steel countersunk  
screws 2.9x25 mm, DIN 7982 C.

**Mounting:** Mount rocker pushbutton, fix  
frame and attachment frame, and snap  
on rocker.

## Wiring diagram



**Must be kept for later use!**

## Eltako GmbH

D-70736 Fellbach

### Technical Support English:

☎ Michael Thünte +49 176 13582514

✉ [thuente@eltako.de](mailto:thuente@eltako.de)

☎ Marc Peter +49 173 3180368

✉ [marc.peter@eltako.de](mailto:marc.peter@eltako.de)

[eltako.com](http://eltako.com)