

THE HOME OF INNOVATION.

*Eltako*



# NEW WIDE-RANGE SWITCHING POWER SUPPLY UNITS

PERFORMANCE DOUBLED - ENERGY EFFICIENCY SIGNIFICANTLY INCREASED

Using the latest electronic components, we have increased the efficiency of our wide-range switching power supplies and in some cases halve the space required.

Of course, they are still short-circuit-proof and have an auto-recovery function that automatically switches them back on after an overload or overtemperature has been eliminated.

*Eltako*

PROFESSIONAL  
**STAN  
DARD**

## WIDE RANGE SWITCHING POWER SUPPLY UNITS WNT15



Manuals and documents in further languages:  
[https://eltako.com/redirect/WNT15-12VDC\\*24W](https://eltako.com/redirect/WNT15-12VDC*24W)

### WNT15-12VDC/24W



**Wide range switching power supply unit. Rated capacity 24 W. Standby loss 0.1 watt only.**

Modular devices for DIN 60715 TH35 rail mounting.

1 module = 18 mm wide, 58 mm deep.

At a load of more than 50% of the rated capacity and always if there are adjacent switching power supply units and if there are dimmers a ventilation clearance of 1/2 module must be maintained with the spacers DS12 on both sides.

Wide range input voltage 88-264 V AC (110 V -20% up to 240 V +10%).

Efficiency 91%. Stabilised output voltage  $\pm 1\%$ , low residual ripple. Short-circuit proof.

Overload protection and over-temperature switch-off by means of switching off with automatic switching-on after fault clearance (autorecovery function).

<b>WNT15-12VDC/24W</b>	Wide-range switching power supply unit 12 V DC	<b>Art. No. 20000072</b>	<b>40,00 €/pc.</b>
------------------------	--	--------------------------	--------------------



Manuals and documents in further languages:  
[https://eltako.com/redirect/WNT15-24VDC\\*24W](https://eltako.com/redirect/WNT15-24VDC*24W)

### WNT15-24VDC/24W



**Wide range switching power supply unit. Rated capacity 24 W. Standby loss 0.1 watt only.**

Modular devices for DIN 60715 TH35 rail mounting.

1 module = 18 mm wide, 58 mm deep.


At a load of more than 50% of the rated capacity and always if there are adjacent switching power supply units and if there are dimmers a ventilation clearance of 1/2 module must be maintained with the spacers DS12 on both sides.

Wide range input voltage 88-264 V AC (110 V -20% up to 240 V +10%).

Efficiency 91%. Stabilised output voltage  $\pm 1\%$ , low residual ripple. Short-circuit proof.

Overload protection and over-temperature switch-off by means of switching off with automatic switching-on after fault clearance (autorecovery function).

<b>WNT15-24VDC/24W</b>	Wide-range switching power supply unit 24 V DC	<b>Art. No. 20000073</b>	<b>40,00 €/pc.</b>
------------------------	--	--------------------------	--------------------



Manuals and documents in further languages:  
[https://eltako.com/redirect/WNT15-24VDC\\*48W](https://eltako.com/redirect/WNT15-24VDC*48W)

### WNT15-24VDC/48W



**Wide range switching power supply unit. Rated capacity 48 W. Standby loss 0.2 watt only.**

Modular devices for DIN 60715 TH35 rail mounting.

2 modules = 36 mm wide, 58 mm deep.

At a load of more than 50% of the rated capacity and always if there are adjacent switching power supply units and if there are dimmers a ventilation clearance of 1/2 module must be maintained with the spacers DS12 on both sides.


Wide range input voltage 88-264 V AC (110 V -20% up to 240 V +10%).

Efficiency 91%. Stabilised output voltage  $\pm 1\%$ , low residual ripple. Short-circuit proof.



Overload protection and over-temperature switch-off by means of switching off with automatic switching-on after fault clearance (autorecovery function).

<b>WNT15-24VDC/48W</b>	Wide-range switching power supply unit 24 V DC	<b>Art. No. 20000075</b>	<b>53,33 €/pc.</b>
------------------------	--	--------------------------	--------------------



# UNIVERSAL WIDE RANGE POWER SUPPLY UNIT WNT15U/3,3-12V DC AND WIDE RANGE SWITCHING POWER SUPPLY UNITS WNT61





## Function rotary switch



Manuals and documents in further languages:  
[https://eltako.com/redirect/WNT15U\\*3,3-12VDC](https://eltako.com/redirect/WNT15U*3,3-12VDC)



Manuals and documents in further languages:  
[https://eltako.com/redirect/WNT61-12VDC\\*10W](https://eltako.com/redirect/WNT61-12VDC*10W)



Manuals and documents in further languages:  
[https://eltako.com/redirect/WNT61-24VDC\\*10W](https://eltako.com/redirect/WNT61-24VDC*10W)

## WNT15U/3,3-12V DC



Universal wide range power supply unit. With 5 adjustable output voltages 3,3 V/2 A, 5 V/2 A, 7,5 V/1,5 A, 9 V/1,3 A, 12 V/1 A. Standby loss 0.1 watt only.

Modular devices for DIN 60715 TH35 rail mounting.

1 module = 18 mm wide, 58 mm deep.

At a load of more than 50 % of the rated capacity and always if there are adjacent switching power supply units from 12 W rated capacity and if there are dimmers a ventilation clearance of ½ module must be maintained with the spacers DS12 on both sides.

Wide range input voltage 88-264 V AC (110 V -20% to 240 V +10%).

Stabilised output voltage ±1%, low residual ripple.

Short-circuit proof.

Overload protection and over-temperature switch-off by means of switching off with automatic switching-on after fault clearance (autorecovery function).

WNT15U/3,3-12V DC	Universal wide range power supply unit	Art. No. 20000175	60,00 €/pc.
-------------------	--	-------------------	-------------

## WNT61-12VDC/10W



Wide range switching power supply unit. Rated capacity 10 W. Standby loss 0.1 watt only.

Built-in device for installation. 45 mm long, 45 mm wide, 33 mm deep.

Wide range input voltage 88-264 V AC (110 V -20% up to 240 V +10%).

Efficiency 86%.

Stabilised output voltage ±1%, low residual ripple.

Short-circuit proof.

Overload protection and over-temperature switch-off by means of switching off with automatic switching-on after fault clearance (autorecovery function).

WNT61-12VDC/10W	Wide-range switching power supply unit 12V DC	Art. No. 61000264	32,00 €/pc.
-----------------	---	-------------------	-------------

## WNT61-24VDC/10W



Wide range switching power supply unit. Rated capacity 10 W. Standby loss 0.1 watt only.

Built-in device for installation. 45 mm long, 45 mm wide, 33 mm deep.

Wide range input voltage 88-264 V AC (110 V -20% up to 240 V +10%).

Efficiency 86%.

Stabilised output voltage ±1%, low residual ripple.

Short-circuit proof.

Overload protection and over-temperature switch-off by means of switching off with automatic switching-on after fault clearance (autorecovery function).

WNT61-24VDC/10W	Wide-range switching power supply unit 24V DC	Art. No. 61000265	32,00 €/pc.
-----------------	---	-------------------	-------------



*Eltako*

## ELTAKO GmbH

Hofener Straße 54

D-70736 Fellbach

+49 711 94350000

info@eltako.de

www.eltako.com

**Scan the QR code – and contact us directly!**

### Technical support:



+49 711 943 500 25

technical-support@eltako.de

### Commercial support:



+49 711 943 500 00

export@eltako.de