



Manuals and documents in further languages:  
[https://eltako.com/redirect/FTS61BTK\\*8](https://eltako.com/redirect/FTS61BTK*8)

## FTS61BTK/8



**Bus pushbutton coupler FTS61BTK/8 for 8 conventional pushbuttons for connection to FTS14TG pushbutton gateways by 2-wire pushbutton bus. Only 0.2 watt standby loss.**

For installation. 45 mm long, 45 mm wide, 18 mm deep.

Up to 30 bus pushbuttons and/or bus pushbutton couplers FTS61BTK/8 devices can be connected to the BP and BN terminals of a pushbutton gateway FTS14TG. The permitted total line length is 200 m. The RLC device enclosed with the FTS14TG must also be connected to the terminals BP and BN on the bus switch or pushbutton bus coupler furthest away.

A voltage of 29 V DC is supplied to the connected FTS61BTK/8 over a 2-wire pushbutton bus which is also used for data transfer.

Please use only conventional bus or telephone lines.

Up to eight conventional pushbuttons T1-T8 can be connected to the 30 cm long connecting cables. Each opposite pole is T0. The connecting cables can be extended up to 2 m.

**Caution: Do not apply any voltage.**

The pairs T1/T3, T2/T4, T5/T7 and T6/T8 can be defined as direction pushbuttons.

Connect the bus to BP and BN. Make sure the polarity is correct.

FTS61BTK/8	Bus pushbutton coupler for 8 conventional pushbuttons	Art. No. 30014075	93,50 €/pc.
------------	---	-------------------	-------------