



Manuals and documents in further languages:
<https://eltako.com/redirect/FDG62-230V>

FDG62-230V



Wireless DALI gateway, bidirectional. For installation. 49 mm long, 51 mm wide, 20 mm deep. Only 0.5 watt standby loss.

For installation. 49x51 mm, 20 mm deep.

The connection terminals are plug-in terminals for conductor cross-sections from 0.2 mm² to 2.5 mm².

The convenient tap technology permits the teach-in of up to 32 wireless universal pushbuttons, wireless direction pushbuttons, wireless central control pushbuttons, motion sensors, tunable white and intensity double rocker pushbuttons.

Bidirectional wireless switchable.

Power supply 230 V at terminals N and L.

The DALI bus power supply DL-N2-80mA and up to 40 DALI devices are connected to the DALI terminals.

The gateway FDG62 controls DALI devices with EnOcean wireless transmitters.

Only **broadcast commands** can be sent.

In addition to the radio control input via an internal antenna, the connected DALI devices can also be controlled with a 230 V control button that may be installed in front of the FDG62.

A glow lamp current is not permitted.

The FDG62 internally saves the dimming value and supplies this value as feedback. The same feedback telegrams are generated as for an FD62NPN.

Actuators can then be activated by the feedback signals.

The FDG62 fulfils the function of the DALI master.

FDG62-230V	Wireless DALI gateway	Art. No. 30100868	79,80 €/pc.
------------	-----------------------	-------------------	-------------