


WIRELESS ACTUATOR FOR EXTRACTOR HOODS CONTROL WITH WINDOW/DOOR CONTACT FDH62NP-230V+FTKB



Typical connection



FDH62NP-230V+FTKB



Wireless extractor hoods control. 1 NO contact not potential free 10 A/250 V AC. Only 0,4 watt standby loss. For installation. 49 x 51 mm wide, 20 mm deep.

The terminals are plug-in terminals for conductor cross-sections of 0,2 mm² to 2,5 mm².

Using easy tap technology, up to 32 wireless universal pushbuttons and wireless window contacts can be taught in.

Only sensors are allowed which report that the window is actually open or tilted. Otherwise there is a risk of poisoning!

Bidirectional wireless switchable. Supply voltage, switching voltage and control voltage local 230 V.

Zero passage switching. By using a bistable relay coil power loss and heating is avoided even in the on mode. After installation, wait for short automatic synchronisation before the switched consumer is connected to the mains. If a power failure occurs, the switching state is retained.

If supply voltage fails, the device is switched off in defined mode.

The extractor hood motor can only be switched on when the window is open.

If the window is closed, the relay switches the motor off. However, if the motor is switched off before the window is closed, any in-built lights that are switched on remain on and can be switched on and off using the switch on the extractor hood. If the motor is switched on in addition to the lights with the window closed, the relay switches off.

The in-built lights can be switched on by a wireless pushbutton or a local conventional 230 V control push-button (a glow lamp current is not permitted) even if the window is closed and the relay is switched off

FTKB-wg

Wireless window/door contact with solar cell and battery 75 x 25 x 12 mm, pure white glossy.

Starting at 100 Lux daylight the window/door contact FTKB powers itself from a solar cell, otherwise several years with a button cell CR2032.

On opening and closing, the related telegram is send twice in short succession. The current status telegram is sent cyclically every approx. 8 minutes.

Adhesive foil mounting.

Window/door contact dimensions l x w x h: 75 x 25 x 12 mm; magnet dimensions l x w x h: 37 x 10 x 6 mm.

FDH62NP-230V+FTKB	Wireless actuator for extractor hoods control with window/door contact	EAN 4010312319826	98,80 €/pc.
--------------------------	--	-------------------	--------------------