




Typical connection



Manuals and documents in further languages:
<https://eltako.com/redirect/FL62-230V>

FL62-230V



Wireless light actuator 10 A/250 V AC. Impulse switch with NO contact, potential free. 230 V LED lamps and ESL up to 200 W, 230 V incandescent lamps and halogen lamps 1000 W. Standby loss only 0.4 watt.

For installation. 49 x 51 mm wide, 20 mm deep.

The terminals are plug-in terminals for conductor cross-sections of 0.2 mm² to 2.5 mm².

The convenient tap technology permits the teach-in of up to 32 wireless universal pushbuttons, wireless direction pushbuttons, wireless central control pushbuttons and motion sensors.

Bidirectional wireless switchable.

Distance between control terminals and contact 6 mm.

Supply voltage, switching voltage and control voltage local 230 V.

If supply voltage fails, the device is switched off in defined mode. When the supply voltage is restored, the device is switched off in a defined process. After installation, wait for the short automatic synchronisation before connecting the switched user to the network.

In addition to the wireless control input via an internal antenna, this wireless actuator can also be controlled locally by a conventional 230 V control switch if fitted previously.

Glow lamp current is not permitted.

FL62-230V	Wireless light actuator, 1 NO contact 10 A	Art. No. 30100532	65,80 €/pc.
------------------	--	--------------------------	--------------------