

## FSNT12-12V/12W



### Rated capacity 12 W. Standby loss 0.2 watt only.

Modular device for DIN 60715 TH35 rail mounting. 1 module = 18mm wide, 58mm deep.  
At a load of more than 50% of the rated capacity and always if there are adjacent switching power supply units from 12W rated capacity and if there are dimmers a ventilation clearance of 1/2 module must be maintained with the spacers DS12 on both sides.

Input voltage 230V (-20% up to +10%). Efficiency 83%.

Stabilised output voltage  $\pm 1\%$ , low residual ripple. Short-circuit proof.

Overload protection and over-temperature switch-off by means of switching off with automatic switching-on after fault clearance (autorecovery function).

For redundant operation 2 switching power supply units can be connected in parallel.

**FSNT12-12V/12W**

Switching power supply unit

EAN 4010312313151

**37,70 €/pc.**

## FSNT12-12V/24W



### Rated capacity 24 W. Standby loss 0.2 watt only.

Modular device for DIN 60715 TH35 rail mounting. 2 modules = 36mm wide, 58mm deep.  
At a load of more than 50% of the rated capacity and always if there are adjacent switching power supply units from 12W rated capacity and if there are dimmers a ventilation clearance of 1/2 module must be maintained with the spacers DS12 on both sides.

Input voltage 230V (-20% up to +10%). Efficiency 83%.

Stabilised output voltage  $\pm 1\%$ , low residual ripple. Short-circuit proof.

Overload protection and over-temperature switch-off by means of switching off with automatic switching-on after fault clearance (autorecovery function).

For redundant operation 2 switching power supply units can be connected in parallel.

**FSNT12-12V/24W**

Switching power supply unit

EAN 4010312313176

**47,50 €/pc.**

## FSNT61-12V/6W



### Rated capacity 6 W. Standby loss 0.1 watt only.

For installation. 45mm long, 45mm wide, 33mm deep.

Input voltage 230V (-20% up to +10%). Efficiency 81%.

Stabilised output voltage  $\pm 1\%$ , low residual ripple. Short-circuit proof.

Overload protection and over-temperature switch-off by means of switching off with automatic switching-on after fault clearance (autorecovery function).


**FSNT61-12V/6W**

Switching power supply unit

EAN 4010312313145

**34,30 €/pc.**

## FSNT61-24V/6W



### Rated capacity 6 W. Standby loss 0.1 watt only.

For installation. 45mm long, 45mm wide, 33mm deep.

Input voltage 230V (-20% up to +10%).

Efficiency 82%. Stabilised output voltage  $\pm 1\%$ , low residual ripple.

Short-circuit proof.

Overload protection and over-temperature switch-off by means of switching off with automatic switching-on after fault clearance (autorecovery function).

**FSNT61-24V/6W**

Switching power supply unit

EAN 4010312313169

**34,30 €/pc.**