



Manuals and documents in further languages:  
[https://eltako.com/redirect/KNX\\_ENO\\_626](https://eltako.com/redirect/KNX_ENO_626)

# KNX ENO 626



**Bidirectional gateway between EnOcean wireless and KNX bus with 8 channels for flush mounting.**

**The KNX ENO 626 secure acts as a bidirectional gateway between EnOcean Wireless and the KNX/EIB bus. Control commands and measured values can be transmitted by EnOcean wireless sensors to the KNX bus, for example to control KNX actuators.** Similarly, EnOcean wireless actuators can be controlled by KNX. The KNX ENO 626 secure from Weinzierl allows encrypted communication with security compatible EnOcean devices.

The KNX ENO 626 secure has 8 wireless channels and accepts over 100 device profiles (EEP EnOcean Equipment Profile), it allows an easy and secure connection from different EnOcean sensors and actor to a KNX installation.

In addition, the gateway offers logic and control functions and comprises an integrated level 1 wireless repeater.

The purpose of the **repeater function** is to span large distances between sensors and actuators.

**Configuration** takes place using the KNX ENO tool. Download from [www.weinzierl.de](http://www.weinzierl.de).

**Flush mounting** in a 55 mm flush-mounted box.

KNX ENO 626	Flush-mounted EnOcean KNX gateway	Art. No. 30000944	323,90 €/pc.
-------------	-----------------------------------	-------------------	--------------