



Manuals and documents in further languages:
https://eltako.com/redirect/KNX_ENO_626

KNX ENO 626



Bidirectional gateway between EnOcean wireless and KNX bus with 8 channels for flush mounting.

The KNX ENO 626 secure acts as a bidirectional gateway between EnOcean Wireless and the KNX/EIB bus. Control commands and measured values can be transmitted by EnOcean wireless sensors to the KNX bus, for example to control KNX actuators. Similarly, EnOcean wireless actuators can be controlled by KNX. The KNX ENO 626 secure from Weinzierl allows encrypted communication with security compatible EnOcean devices.

The KNX ENO 626 secure has 8 wireless channels and accepts over 100 device profiles (EEP EnOcean Equipment Profile), it allows an easy and secure connection from different EnOcean sensors and actor to a KNX installation.

In addition, the gateway offers logic and control functions and comprises an integrated level 1 wireless repeater.

The purpose of the **repeater function** is to span large distances between sensors and actuators.

Configuration takes place using the KNX ENO tool. Download from www.weinzierl.de.

Flush mounting in a 55 mm flush-mounted box.

KNX ENO 626	Flush-mounted EnOcean KNX gateway	Art. No. 30000944	323,90 €/pc.
--------------------	-----------------------------------	--------------------------	---------------------