



No cloud connection needed.
Data is available directly on site at the Smart Home controller.

MiniSafe



The MiniSafe as Smart Home controller receives EnOcean signals from many Eltako sensors and actuators and permits highly encrypted access, both internally and externally, with the app GFA4 by smartphone or tablet. Smart Home controller.

MiniSafe connected to the local network via Ethernet. The intended use of the MiniSafe is the bidirectional communication with EnOcean wireless signals over Ethernet (TCP/IP).

Recommendation: maximum 30 actuators and sensors for approx. 10 seconds connection time between app and MiniSafe.

Scope of supply: MiniSafe, wall adapter power supply, 1x ethernet cable 2 m RJ45, quick start guide, instruction for downloading the app GFA4.

Specifications: Processor: Intel X1021, memory: 1GB DDR3 RAM + 4 GB eMMC, LAN: 1x 10/100 Mbit ethernet, integrated EnOcean-868 MHz wireless module (TCM310) ESP3, power supply 5 V, plastic housing pure white glossy, dimensions: 165x70x35 mm with slots for wall mounting and feet to put down, weight: 175 grams.

The configuration and control is performed via the app GFA4 from the Android app store or Apple app store.

MiniSafe	Smart Home controller	EAN 4010312319079	305,90 €/pc.*
-----------------	-----------------------	-------------------	----------------------