





Manuals and documents in further languages:

https://eltako.com/redirect/NFCS55E-

NFCS55E-

NFC sensor for single mounting $80 \times 80 \times 15 \, \text{mm}$ or mounting into the E-Design55 switching system. Without battery or wire. No standby loss.

The NFC sensor can be used to trigger smart home functions with the mobile phone and to save data. It does not send its own telegram into the radio network, serves primarily as a , trigger' and must be actively scanned.

In conjunction with smart end devices, this can be integrated into a smart home control system.

Storage capacity: 144 bytes Communication speed: 106 kbit/s

Protection class: IP68 (dust and waterproof) Operating temperature: -35°C ~ +85°C

Data retention: 10 years

Read / write resistance: 100,000 cycles Compatible with all NFC-enabled devices

NFCS55E-am	NFC sensor in E-Design55, anthracite mat	Art. No. 30055647	20,00 €/pc.
NFCS55E-pg	NFC sensor in E-Design55, polar white glossy	Art. No. 30055648	20,00 €/pc.
NFCS55E-pm	NFC sensor in E-Design55, polar white mat	Art. No. 30055649	20,00 €/pc.
NFCS55E-wg	NFC sensor in E-Design55, pure white glossy	Art. No. 30055646	20,00 €/pc.