



R12-110-230V



Manuals and documents in further languages:
http://eltako.com/redirect/R12-100-*200-*110-*020-

Technical data page 19-5.

R12-100-/200-/110-/020-



1- and 2-pole 16 A/250 V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.

1 module = 18 mm wide, 55 mm deep.

100% time on. Control power demand 1.9 W.

Contacts: 1 NO, 2 NO, 1 NO + 1 NC, 2 NC (closed-circuit current relay, 230 V only).

Contact gap 3 mm.

Contact/contact test voltage 2000 V and control connections/contact test voltage 4000 V.

25 A devices XR12, page 19-4. Retrofittable auxiliary contact KM12, page 18-3.

The pin-compatible ER12DX-UC, ER12-200-UC and ER12-110-UC electronic switching relays can also be used.

The universal control voltage UC covers the voltage ranges of 12 to 230 V AC at 50-60 Hz and 12 to 230 V DC.

R12-100-12V	1 NO 16 A	Art. No. 22100011	28,30 €/pc.
R12-100-230V	1 NO 16 A	Art. No. 22100030	28,30 €/pc.
R12-100-8V, 24V, 12V DC, 24V DC	1 NO 16 A	Art. No. 22100010, 22100020, 22100054, 22100055	30,50 €/pc.
R12-200-12V	2 NO 16 A	Art. No. 22200011	36,00 €/pc.
R12-200-230V	2 NO 16 A	Art. No. 22200030	36,00 €/pc.
R12-200-8V, 24V, 12V DC, 24V DC	2 NO 16 A	Art. No. 22200010, 22200020, 22200054, 22200055	37,80 €/pc.
R12-110-12V	1 NO + 1 NC 16 A	Art. No. 22110011	36,00 €/pc.
R12-110-230V	1 NO + 1 NC 16 A	Art. No. 22110030	36,00 €/pc.
R12-110-8V, 24V, 12V DC, 24V DC	1 NO + 1 NC 16 A	Art. No. 22110010, 22110020, 22110054, 22110055	37,80 €/pc.
R12-020-230V	2 NC 16 A	Art. No. 22020030	38,10 €/pc.