



R12-110-230V



Manuals and documents in further languages:  
[https://eltako.com/redirect/R12-100-\\*200-\\*110-\\*020-](https://eltako.com/redirect/R12-100-*200-*110-*020-)

Technical data page 19-5.

## R12-100-/200-/110-/020-



### 1- and 2-pole 16 A/250 V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.

1 module = 18 mm wide, 55 mm deep.

100% time on. Control power demand 1.9 W.

Contacts: 1 NO, 2 NO, 1 NO + 1 NC, 2 NC (closed-circuit current relay, 230 V only).

Contact gap 3 mm.

Contact/contact test voltage 2000 V and control connections/contact test voltage 4000 V.

**25 A devices XR12, page 19-4. Retrofittable auxiliary contact KM12, page 18-3.**

The pin-compatible ER12DX-UC, ER12-200-UC and ER12-110-UC electronic switching relays can also be used.

The universal control voltage UC covers the voltage ranges of 12 to 230 V AC at 50-60 Hz and 12 to 230 V DC.

<b>R12-100-12V</b>	1 NO 16 A	<b>Art. No. 22100011</b>	<b>31,00 €/pc.</b>
<b>R12-100-230V</b>	1 NO 16 A	<b>Art. No. 22100030</b>	<b>31,00 €/pc.</b>
<b>R12-100-8V, 24V, 12V DC, 24V DC</b>	1 NO 16 A	<b>Art. No. 22100010, 22100020, 22100054, 22100055</b>	<b>33,50 €/pc.</b>
<b>R12-200-12V</b>	2 NO 16 A	<b>Art. No. 22200011</b>	<b>39,40 €/pc.</b>
<b>R12-200-230V</b>	2 NO 16 A	<b>Art. No. 22200030</b>	<b>39,40 €/pc.</b>
<b>R12-200-8V, 24V, 12V DC, 24V DC</b>	2 NO 16 A	<b>Art. No. 22200010, 22200020, 22200054, 22200055</b>	<b>41,50 €/pc.</b>
<b>R12-110-12V</b>	1 NO + 1 NC 16 A	<b>Art. No. 22110011</b>	<b>39,40 €/pc.</b>
<b>R12-110-230V</b>	1 NO + 1 NC 16 A	<b>Art. No. 22110030</b>	<b>39,40 €/pc.</b>
<b>R12-110-8V, 24V, 12V DC, 24V DC</b>	1 NO + 1 NC 16 A	<b>Art. No. 22110010, 22110020, 22110054, 22110055</b>	<b>41,50 €/pc.</b>
<b>R12-020-230V</b>	2 NC 16 A	<b>Art. No. 22020030</b>	<b>40,60 €/pc.</b>