



S12-100-230V

Technical data page 18-7.

## S12-100-/200-/110-



### 1- and 2-pole 16 A/250 V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.

1 module = 18 mm wide, 55 mm deep.

100% time on. Control power demand 5-6 W only.

Contacts 1 NO, 2 NO, 1 NO + 1 NC.

Contact gap 3 mm. Spacing of control connections/contact > 6 mm.

**Devices for 25 A XS12, page 18-5.**

**Retrofittable auxiliary contact KM12, page 18-3.**

**The pin-compatible ES12DX-UC, ES12-200-UC and ES12-110-UC electronic impulse switches can also be used.**

**Their universal control voltage UC covers the voltage ranges of 8 to 253 V AC at 50-60Hz and 10 to 230 V DC.**

|  |                  |                   |                    |
|--|------------------|-------------------|--------------------|
| <b>S12-100-12V</b>                     | 1 NO 16 A        | EAN 4010312100455 | <b>24,80 €/pc.</b> |
| <b>S12-100-230V</b>                    | 1 NO 16 A        | EAN 4010312100479 | <b>24,80 €/pc.</b> |
| <b>S12-100-8V, 24V, 12V DC, 24V DC</b> | 1 NO 16 A        |                   | <b>26,70 €/pc.</b> |
| <b>S12-200-12V</b>                     | 2 NO 16 A        | EAN 4010312100530 | <b>31,00 €/pc.</b> |
| <b>S12-200-230V</b>                    | 2 NO 16 A        | EAN 4010312100554 | <b>31,60 €/pc.</b> |
| <b>S12-200-8V, 24V, 12V DC, 24V DC</b> | 2 NO 16 A        |                   | <b>33,10 €/pc.</b> |
| <b>S12-110-12V</b>                     | 1 NO + 1 NC 16 A | EAN 4010312100493 | <b>31,00 €/pc.</b> |
| <b>S12-110-230V</b>                    | 1 NO + 1 NC 16 A | EAN 4010312100516 | <b>31,60 €/pc.</b> |
| <b>S12-110-8V, 24V, 12V DC, 24V DC</b> | 1 NO + 1 NC 16 A |                   | <b>33,10 €/pc.</b> |