





Manuals and documents in further languages: https://eltako.com/redirect/ WSZ155DSS-16A_MID

Technical data page 10-30.

WSZ155DSS-16A MID





Portable single-phase energy meter with German type plug and coupling (Type F). Suitable for indoor and outdoor use. Maximum current 16 A. Protection class IP54. Standby loss 0,4 watt only.

Housing dimensions 155x60x82 mm, connection cable 1.5 m (including plug and coupling). Accuracy class B (1%).

This portable single-phase energy meter measures active energy by means of the current between input and output. The internal power consumption of 0.4 watt active power is neither metered nor indicated.

The display changes cyclically every 10 seconds between the accumulated active energy in kWh and the instantaneous consumption in kWh.

The start current is 20 mA.

The display can only be read when the power supply is on. However, the consumption is saved to a non-volatile memory and is displayed immediately after a power failure.

The digital display has 7 digits. Two decimal places are indicated up to 99999.99 kWh.

Above 100000.0 kWh there is only one decimal place.

The mobile single phase meter is equipped with a mounting bracket for easy installation. This can easily be removed if not necessary.

The power consumption is shown with a LED that flashes 2000 times per kWh.

WSZ155DSS-16A MID	Portable single-phase energy meter, MID	Art. No. 28016115	119,80 €/pc.
-------------------	---	-------------------	--------------