

## THE ALL-IN-ONE PROFESSIONAL SMART HOME CONTROLLER

The new MiniSafe2, which is built on the success of the popular Minisafe is well suited for experts and beginners alike. With the new GFA5 app you get a powerful controller linking Eltako EnOcean devices together on your tablet or phone.

It is configured and controlled via the app, which is available free of charge for iOS and Android devices. In addition, the voice services Amazon Alexa and Google Assistant can be utilised.

With just a few clicks or words, you can switch and dim your lights, regulate the heating or move the blinds throughout the building. Personal settings and scenes can be stored in the GFA5 app which can be accessed and changed at any time.

The MiniSafe2 is ideal for the professional smart home, with its clean lines and easy operation.





www.eltako.com

## PROFESSIONAL SMART HOME CONTROLLER MINISAFE2





Smart Home controller







## MiniSafe2



The MiniSafe2 is the smallest, universally applicable Smart Home controller from Eltako. The central control unit ensures that EnOcean compatible sensors and actuators can be conveniently and centrally controlled using the GFA5 app and voice commands.

This allows light, shading, air conditioning, security components, and much more to be easily and flexibly combined with one another in order to transform any living environment into a professional smart home in no time at all.

The basic equipment includes app-based automation, update and backup options. Migration from older Eltako controllers is possible.

The MiniSafe2 can basically be operated offine and locally, internet access is not required for this. Remote access and the cloud connection can optionally be activated during operation.

An internet connection and a WiFi network are required for setup.

| TECHNICAL DATA                        |   |  |  |
|---------------------------------------|---|--|--|
| Dimensions                            | H x W x D: 90 x 90 x 20 mm  |  |  |
| Operating temperature                 | Min. 0 °C to max. +40 °C  |  |  |
| Weight                                | approx. 80 g  |  |  |
|                                       |   |  |  |
| Power supply                          | 5 V DC / 1.5 A, 100 V - 240 V AC, 50/60 Hz                        |  |  |
| Power consumption                     | 1.3 watt  |  |  |
| Processor                             | 84 MHz ARM® Cortex® - M4, 512 Kbyte Flash, 96 KB SRAM             |  |  |
| Network                               | WLAN IEEE 802.11 /b/g/n 2.4 GHz                                   |  |  |
| Wireless transceiver                  | 1 x En0cean 868 MHz, 1 x 868 MHz                                  |  |  |
| Infrared (IR)                         | Integrated IR receiver 38 KHz and transmitter unit (36 - 455 KHz) |  |  |
| Connection of external IR transmitter | 1 x 3.5 mm jack socket, addressable (rear)                        |  |  |

| MiniSafe2 | Smart Home controller | EAN 4010312323939 | 297,00 €/pc.* |
|-----------|-----------------------|-------------------|---------------|
|-----------|-----------------------|-------------------|---------------|

<sup>\*</sup> The software part is not discountable.



**Technical support:** 

⇒ +49 711 943 500 25 ⊠ technical-support@eltako.de





