

Type	PL-SAMDU	PL-AMD10V	PL-SAM1L PL-SAM1LT	PL-SAM2L	PL-SAM2
Contacts					
Contact material/contact gap	Power Mosfet	AgSnO ₂ /0.5 mm	AgSnO ₂ /0.5 mm	AgSnO ₂ /0.5 mm	AgSnO ₂ /0.5 mm
Spacing of control connections/contact	-	-	3 mm	3 mm	3 mm
Test voltage control connections/contact	-	-	2000 V	2000 V	2000 V
Rated switching capacity each contact	-	600 VA ⁴⁾	10A/250V AC	5A/250V AC	3A/250V AC
Incandescent lamp and halogen lamp load ¹⁾ 230V, I on ≤ 70 A/104-11 ms	up to 300 W ²⁾	-	2000 W	1000 W	-
Inductive load cos φ = 0.6/230 V AC inrush current ≤ 35 A	up to 300 W ⁶⁾	-	650 W	650 W ⁵⁾	650 W ⁵⁾
Fluorescent lamp load with KVG* in lead-lag circuit or non compensated	-	-	1000 VA	500 VA	-
Fluorescent lamp load with KVG* shunt-compensated or with EVG*	-	600 VA ⁴⁾	500 VA	250 VA	-
Compact fluorescent lamps with EVG* and energy saving lamps	-	-	up to 400 W	-	-
Dimmable 230 V LED lamps	up to 300W ³⁾	-	up to 400 W	-	-
Service life at rated load, cos φ = 1 or incandescent lamps 500 W at 100/h	-	>10 ⁵	>10 ⁵	>10 ⁵	>10 ⁵
Service life at rated load, cos φ = 0.6 at 100/h	-	>4x10 ⁴	>4x10 ⁴	>4x10 ⁴	>4x10 ⁴
Max. operating cycles	-	10 ³ /h	10 ³ /h	10 ³ /h	10 ³ /h
Connection type	Plug-in terminals	Plug-in terminals	Plug-in terminals	Plug-in terminals	Plug-in terminals
Minimum conductor cross-section	0.2 mm ²	0.2 mm ²	0.2 mm ²	0.2 mm ²	0.2 mm ²
Maximum conductor cross-section	1.5 mm ²	1.5 mm ²	1.5 mm ²	1.5 mm ²	1.5 mm ²
Conductor stripping	8-9 mm	8-9 mm	8-9 mm	8-9 mm	8-9 mm
Type of enclosure/terminals	IP30/IP20	IP30/IP20	IP30/IP20	IP30/IP20	IP30/IP20
Electronics					
Time on	100%	100%	100%	100%	100%
Max./min. temperature at mounting location	+50°C/-20°C	+50°C/-20°C	+50°C/-20°C	+50°C/-20°C	+50°C/-20°C
Standby loss (active power)	0.6 W	0.5 W	0.5 W	0.5 W	0.5 W
Local control current at 230V control input	0.4 mA	-	0.4 mA	0.4 mA	0.4 mA
Max. parallel capacitance (approx. length) of local control lead at 230V AC	3 nF (10 m)	-	3 nF (10 m)	3 nF (10 m)	3 nF (10 m)

¹⁾ Applies to lamps of max. 150 W.
²⁾ Also transformers electronically (C load).
³⁾ Generally applies to 230V LED lamps. Due to different lamp electronics, switch on/off problems and a restriction in the maximum number of lamps, however, the dimming ranges may be limited depending on the manufacturer; in particular when the connected load is very low (e.g. with 5 W LEDs). The comfort position LC1 at SAMDU optimizes the dimming range, which however results in a maximum capacity of only up to 150 W. In this comfort position, no wound (inductive) transformers should be dimmed.
⁴⁾ Fluorescent lamps or LV halogen lamps with electronic ballast.
⁵⁾ All actuators with 2 contacts: Inductive load cos φ = 0.6 as sum of both contacts 1000 W max.
⁶⁾ A maximum of 2 transformers of the same type.
 * EVG = electronic ballast units; KVG = conventional ballast units

Powerline communication in the B/C-Band (5kb/s) corresponds to FCC, CENELEC EN 50065-1 and LONWORKS protocol